

Part Number: 83269

50 Ohm, RG188A, 26 AWG

Product Description

RG-188A/U type, 26 AWG stranded (7x34) .0205" silver-plated copper-covered steel conductor, TFE Teflon® insulation, SPC braid shield (95% coverage), TFE tape jacket.

Technical Specifications

Product Overview

| Environmental Space: | Indoor (Not Riser or Plenum) |
|------------------------|------------------------------|
| Suitable Applications: | Mil Spec, RG-188A/U |

Physical Characteristics (Overall)

Conductor

| AWG | Stranding | Mate | rial | Nominal Diameter | No. of Coax |
|-------|--------------|-----------------------|----------------------|------------------|-------------|
| 26 | 7x34 | SPCCS - Silver Plated | Copper Covered Steel | 0.0205 in | 1 |
| Condu | uctor Count: | | 1 | | |
| Condu | uctor Size: | | 26 AWG | | |

Insulation

| Material | Material Trade Name | Nominal Diameter |
|---------------------------|---------------------|------------------|
| TFE - Tetrafluoroethylene | Teflon® | 0.058 in |

Outer Shield Material

| Type | Material | Coverage [%] |
|-------|----------------------------|--------------|
| Braid | SPC - Silver Plated Copper | 95 % |

Outer Jacket Material

| Material | Material Trade Name | Nominal Diameter |
|---------------------------|---------------------|------------------|
| TFE - Tetrafluoroethylene | Teflon® | 0.100 in |

Electrical Characteristics

Conductor DCR

| Nominal Conductor DCR | Nominal Outer Shield DCR | Outer Conductor DCR |
|-----------------------|--------------------------|---------------------|
| 91.2 Ohm/1000ft | 8.5 Ohm/1000ft | 8.5 Ohm/1000ft |

Capacitance



Inductance



Impedance

| Nominal Characteristic Impedance |
|----------------------------------|
| 50 Ohm |

High Frequency (Nominal/Typical)

| Frequency [MHz] | Nom. Insertion Loss |
|-----------------|---------------------|
| 1 MHz | 1.2 dB/100ft |
| 10 MHz | 2.7 dB/100ft |
| 50 MHz | 5.6 dB/100ft |
| 100 MHz | 8.3 dB/100ft |
| 200 MHz | 12 dB/100ft |
| 400 MHz | 17.5 dB/100ft |
| 700 MHz | 23.7 dB/100ft |
| 900 MHz | 27.3 dB/100ft |
| 1000 MHz | 29 dB/100ft |

Delay

| Nominal Delay | Nominal Velocity of Propagation (VP) [%] |
|---------------|--|
| 1.47 ns/ft | 69.5 % |

Voltage

Non-UL Voltage Rating 900 V RMS

Temperature Range

| UL Temp Rating: | 200°C |
|-----------------------|-----------------|
| Operating Temp Range: | -70°C To +200°C |

Mechanical Characteristics

| Bulk Cable Weight: | 11 lbs/1000ft |
|----------------------------------|---------------|
| Max Recommended Pulling Tension: | 21 lbs |
| Min Bend Radius/Minor Axis: | 1 in |

Standards

| RG Type: | 188A/U Type |
|-------------------|-------------|
| RG / Series Type: | 188A/U Type |

Applicable Environmental and Other Programs

| EU Directive 2000/53/EC (ELV): | Yes |
|---------------------------------------|-------------------------------|
| EU Directive 2003/96/EC (BFR): | Yes |
| EU Directive 2011/65/EU (ROHS II): | Yes |
| EU Directive 2012/19/EU (WEEE): | Yes |
| EU Directive Compliance: | EU Directive 2003/11/EC (BFR) |
| EU CE Mark: | No |
| EU RoHS Compliance Date (yyyy-mm-dd): | 2005-04-01 |
| CA Prop 65 (CJ for Wire & Cable): | Yes |
| MII Order #39 (China RoHS): | Yes |

Suitability

| Suitability - Aerial: | No | |
|------------------------------------|-----|--|
| Suitability - Burial: | No | |
| Suitability - Hazardous Locations: | No | |
| Suitability - Indoor: | Yes | |
| Suitability - Outdoor: | No | |
| Suitability - Sunlight Resistance: | No | |

Plenum/Non-Plenum

| Plenum (Y/N): | No |
|---------------|----|

Part Number

Variants

| Item # | Color | Footnote |
|---------------|-------|----------|
| 83269 009100 | White | E |
| 83269 0091000 | White | E |

83269 009500 | White | E | Footnote: | E - MAY CONTAIN MORE THAN 1 PIECE. MINIMUM LENGTH OF ANY ONE PIECE IS 25'.

© 2018 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.