



WIRING	SPECIFICATIONS					SHAFT ROTATION FOR INCREASE VOLTAGE	TERMINAL CONNECTIONS		
	INPUT		OUTPUT				FOR INCREASING VOLTAGE AS VIEWED FROM ROTOR END		
	VOLTS	HERTZ	VOLTS	MAX. AMPS	MAX. KVA		INPUT	JUMPER	OUTPUT
THREE PHASE WYE	240	60	0-280	100	48.5	CW	2-2-2	—	B-B-B

UNLESS OTHERWISE SPECIFIED, TOLERANCE IS #				UNITS		TITLE: SPEC. CONTROL DRAWING		 STACO ENERGY PRODUCTS CO. A COMPONENTS CORPORATION OF AMERICA COMPANY DAYTON, OHIO U.S.A.				
DECIMALS	HOLES	ANGLES	DRAFT	IN [mm]		TYPE: 5011-6Y						
.XX	+.004	1°	1-1/2°	ALL DIMENSIONS APPLY AFTER PLATING		DRAWN BY: TIM RAU		DATE: 9/9/97	FIRST USED ON	DO NOT SCALE DWG.	CUSTOMER APPROVAL	DATE
MATERIAL:				ALL DIMENSIONS APPLY AFTER PLATING		CHECKER		DATE	WEIGHT APPROX. 479 LBS.	CODE IDENT. NO. 83008	DWG. NO. 031-6774	
The information and design disclosed herein was originated by and is the property of STACO ENERGY PRODUCTS CO., which reserves all patent, proprietary, design, manufacturing, reproduction, use and sale rights thereto, and to any article disclosed therein except to the extent rights are expressly granted to others. The foregoing does not apply to vendor proprietary parts.				SCALE .25=1		ENGINEER		DATE	SHEET 1 OF 1			